



FIBER-COUPLED LASER DIODE WITH DRIVER & TEC CONTROLLER LDF-30



Fiber-coupled laser diodes with output power up-to 30 W integrated in our laser drivers provide a compact and efficient air-cooled solution for solid-state laser pumping, material processing and scientific applications. The drivers have all protective features for reliable and safe operation, including soft start, true current-source operation, overtemperature and undertemperature limits, current limits, temperature sensor fault alarm, laser diode loop check, etc.

Due to newest electronic design and production technology ALPHALAS provides *the most compact solution* for a ready-to-use fiber-coupled laser diode worldwide, combined with the most universal laser diode driver. The option with built-in frequency generator expands the capabilities for pulsed mode of operation. Thus, the laser diode can be operated in CW, pulsed, or combined CW/pulsed mode (biasing). The back-lighted liquid-crystal display monitors numerous important parameters as laser diode current, TEC module current and current limit, measured and set LD temperature, and temperature limit.

Higher output powers from fiber-coupled laser diodes are also available, as well as custom designs.

See back page for details



FIBER-COUPLED LASER DIODE WITH DRIVER & TEC CONTROLLER LDF-30

TECHNICAL SPECIFICATIONS

Optical:

Optical output power (CW or pulsed): min. 28 W, typ. 30 W, variable
Wavelength: 808 nm (+/-3 nm) standard, on request 800 nm - 980 nm
Fiber coupling: SMA 905, for fibers 400 μ m, or 600 μ m (fiber is optional)

Frequency generator for light output modulation (option LDF-30-P):

- **repetition rate: 100 Hz - 2000 Hz standard (other on request)**
- **pulse duration: 50 μ s - 300 μ s standard (other on request)**

Displayed parameters:

- **CW laser diode current, A**
- **PULSED laser diode current, A (option LDF-30-P)**
- **Repetition rate, kHz (option LDF-30-P)**
- **TEC modules current, A**
- **TEC modules current limit, A**
- **Actual laser diode temperature, °C**
- **Set laser diode temperature, °C**
- **Laser diode temperature limit, °C**

***Control lights (LEDs):* Cooling, Temperature limit error, Interlock**

Additional functions:

- **Trigger input, (option LDF-30-P)**
- **Trigger output (option LDF-30-P)**
- **Laser diode current monitor**
- **Photodiode feedback input (not available for option LDF-30-P)**
- **Interlock**

General:

- **Power requirements: 100 VAC - 240 VAC, 50/60 Hz universal worldwide**
- **Power consumption: max. 700 W**
- **Dimensions: 155x365x450 mm (H x W x L)**
- **Weight: 15 kg**

ALPHALAS GmbH

Bertha-von-Suttner-Str. 5, D-37085 Göttingen, Germany

Tel.: +49-551-7706147, Fax: +49-551-7706146, E-mail: sales@alphalas.com, Web-Site: www.alphalas.com